

## Article Information Sheet (AIS)

This Article Information Sheet (AIS) provides relevant battery information to retailers, consumers, OEMs and others users requesting a GHS-compliant SDS. Articles, such as batteries, are exempt from GHS SDS classification criteria. The GHS criteria is not designed or intended to be used to classify the physical, health and environmental hazards of an article. Branded consumer batteries are defined as electro-technical devices. The design, safety, manufacture, and qualification of branded consumer batteries follow ANSI and IEC battery standards. This document is based on principles set forth in the following hazard communication approaches: ANSI Z-400.1, GHS, JAMP AIS, and IEC 62474.

### 1. Document Information

<b>Document Name</b>	<b>Procell Lithium HPL Cells and Batteries</b>
<b>Document ID</b>	AIS-Li HPL
<b>Issue Date</b>	1-Sep-15
<b>Version</b>	4
<b>Preparer</b>	Product Safety & Regulatory
<b>Last Revision</b>	1/3/2024
<b>Information Contact</b>	<a href="mailto:SDS@duracell.com">SDS@duracell.com</a>

### 2. Company Information

<b>Name &amp; Address</b>	Duracell Industrial Operations, 14 Research Drive, Bethel, CT USA 06801. Duracell Batteries BV, Nijverheidslaan 7, 3200 Aarschot, Belgium. Duracell International Operations Sàrl, Rue du Pré-de-la-Bichette 1, CH-1202, Geneva, Switzerland. & EU Website duracell.info
<b>Telephone</b>	(203) 796-4000
<b>Global Website</b>	<a href="http://www.procell.com">www.procell.com</a>
<b>Consumer Relations</b>	North America: 1-800-551-2355 (9:00 AM - 5:00 PM EST)

#### Consumer Relations

**Latin America**  
(Brazil) 0 800 727 1165, (Chile) 188 800 224 488, (México) 0 1800 283 2901  
(Rest of Latin America) duracell.mx.help

**Europe**  
(UK) 0800 716434, (FR) 0800 346 790 (Service & appel gratuits), (IRL) 1 800 509 176, (DE) 800 101 2112, (AT) 0800 1025 1956, (CH) 0800 000 885, (BE) 0800 509 95, (NL) 0800 265 8616, (IT) 800 125 662, (ES) 900 800 522, (PT) 800 781 012, (GR) 210 66 75 000, (CY) 22-210900, (DK-FI-NO-SE) +46 8 799 1926, (NO) 63791957, (ZA) 0800980782, (RO) 021 3361915, (IS) +354 5222700, (MD) +373 0800700 88, (BG) 02 40 24 500, (BIH) 033756000, (MNE) 020261920, (PL) 00800 77628282, (LT) +370 656 40111, (LV) +371 670 48400, (EE) +3726505555, (CZ) +420 233 325 614, (SK) +42153419601, (HU) 0620 770 7099, (HR) 0800 0009, (SI) 01/588 6800, (AZ) 99412 5990511, (UA) +380444909771 (ПрАТ "САВ 92) & +380442476704 (ТОВ «ІНБЕКТКОМ»), (KZ) +7 727 250 05 50, (KG) 0312 41 77 04 (Apple City International), (TR) 0 850 502 61 40, (BG)02/40 24 500, (BIH) 38733756000, (UZ) 998 900123313

**Asia**  
(CN) 4008850883, (HK) 800-969-950, (TW) 0800-251-122, (AU) 1-800-239901, (NZ) 0800-44-6869, (KP) 080-393-3000, (SG) 800-120-5608, (TH) 001 800 852 6595, (VN) 120 11543, (MY) 1-800-81-5379, (ID)001-803-0167294, (PH) 1-800-1110-1392, (IN) 1800-120-7897

### 3. Article Information

<b>Description</b>	Duracell branded consumer lithium battery
<b>Product Category</b>	Electro-technical device
<b>Use</b>	Portable power source for electronic devices
<b>Model Numbers/IEC Designations (physical descriptions)</b>	CR2 (CR15H270), 123 (123A, CR123A, DL123A, CR17345), CR-A (CR17450)
<b>Principles of Operation</b>	A battery powers a device by converting stored chemical energy into electrical energy.

### 4. Article Construction

<b>Applicable Battery Industry Standards</b>	ANSI C18.3M Part 1, ANSI C18.3M Part 2, ANSI C18.4, IEC 60086,1, IEC 60086-2, IEC 60086-4
<b>Electro-technical System</b>	Lithium Manganese Dioxide
<b>Electrode - Negative</b>	Lithium Alloy (CAS # 7439-93-2)



## Article Information Sheet (AIS)

<b>Electrode - Positive</b>	Manganese Dioxide (CAS # 1313-13-9)
<b>Electrolyte</b>	Propylene Carbonate Solvent (CAS # 108-32-7)
<b>Electrolyte</b>	1,2-Dimethoxyethane Solvent (CAS # 110-71-4)
<b>Polytetrafluoroethylene (PTFE)</b>	CAS#9002-84-0; 0.1-1%
<b>Materials of Construction - Can</b>	Steel (CAS # 110-71-4)
<b>Declarable Substances (IEC 62474 Criteria 1)</b>	1-2-Dimethoxyethane (CAS # 110-71-4)
<b>Mercury Free Battery (ANSI C18.4M &lt;5ppm)</b>	Yes
<b>Small Cell or Battery (ANSI C18.1M Part 2; IEC 60086-5)</b>	N/A
<b>5. Health &amp; Safety</b>	
<b>Warning Label:</b>	<p><u>Required for small lithium batteries: Keepout of reach of children. If swallowed, consult a physician immediately. ANSI or IEC requirements</u></p> <div style="display: flex; align-items: center; justify-content: center;">  <span style="margin: 0 10px;">OR</span>  <span style="margin: 0 10px;">OR</span>  </div>
<b>Normal Conditions of Use</b>	Exposure to contents inside the sealed battery will not occur unless the battery leaks, is exposed to high temperatures, or is mechanically abused.
<b>First Aid - If swallowed</b>	<u>Required for sizes 123 &amp; CR2: Keep away from children. If swallowed, consult a physician immediately. Call National Ingestion Hotline (800-408-8666).</u>
<b>Note to Physician</b>	<p>For information on battery identification and treatment, call the 24- hour National Battery Ingestion Hotline (800-408-8666). Additional treatment information is available from the National Capital Poison Control Center Button Battery Ingestion Triage and Treatment Guideline: <a href="https://www.poison.org/battery/guideline">https://www.poison.org/battery/guideline</a>. If the patient is less than or equal to 12 years, immediately obtain an x-ray to locate the battery. If the patient is &gt; 12 years and the battery diameter is &gt; than 12 mm or unknown also obtain an x-ray. X-rays should include the entire neck, esophagus, and abdomen. Once the position of the battery in the esophagus is determined by x-ray and if less than 12 hours post-ingestion consider giving sucralfate suspension 10ml by mouth every 10 minutes, up to 3 doses while waiting for sedation for endoscopy. Do not delay battery removal because a patient has eaten recently or was given honey or sucralfate by mouth. Batteries lodged in the esophagus should be removed immediately since battery leakage, caustic burns, and perforation can occur as soon as two hours after ingestion. Endoscopic removal is preferred as it allows direct visualization of tissue injury. After the battery is removed from the esophagus if no perforation is evident irrigate the injured area with 50 mL to 150 mL of 0.25% sterile acetic acid and then observe for delayed complications. If a large battery (equal to or greater than 20 mm) is in the stomach or beyond of a child &lt; 5 years and based on history, might have lodged in the esophagus for &gt; 2 hours, consider diagnostic endoscopy to exclude the remote possibility of esophageal injury. Retrieve batteries, endoscopically if possible, from the stomach or beyond if: 1) A magnet was also ingested, 2) The patient develops signs or symptoms that are likely related to battery ingestion, or, 3) A large battery equal to or greater than 15 mm is ingested by a child younger than 6 years, remains in the stomach for 4 days or longer. Allow batteries to pass spontaneously if they have passed beyond the esophagus (stomach and beyond) and no clinical indication of any significant gastrointestinal injury is evident. Confirm battery passage by inspecting stools. Consider repeat radiographs to confirm passage if battery passage not observed in 10-14 days.</p>
<b>Poison Centers/World Directory</b>	<a href="http://globalcrisis.info/poisonemergency.html#AAA">http://globalcrisis.info/poisonemergency.html#AAA</a>
<b>First Aid - Eye Contact</b>	Flush with running water for at least 30 minutes. Seek medical attention immediately.
<b>First Aid - Skin Contact</b>	Remove contaminated clothing and flush skin with running water for at least 15 minutes. Seek medical attention if irritation persists.

## Article Information Sheet (AIS)

<b>First Aid - Inhalation</b>	Contents of leaking battery may be irritating to respiratory passages. Move to fresh air. Seek medical attention if irritation persists.
<b>Battery Safety Standards &amp; Testing</b>	Procell lithium metal batteries meet the requirements of ANSI C18. 3M Part 2 and IEC 60086-4. These standards specify tests and requirements for lithium batteries to ensure safe operation under normal use and reasonably foreseeable misuse. The test regimes assess three conditions of safety. These are: <b><u>1-Intended use simulation:</u></b> Partial use, vibration, thermal shock, and mechanical shock <b><u>2-Reasonably foreseeable misuse:</u></b> Incorrect installation, external short-circuit, free fall (user-drop), over-discharge, and crush <b><u>3-Design consideration:</u></b> Thermal abuse, mold stress
<b>Precautionary Statements</b>	CAUTION: Keep batteries away from children. If swallowed, consult a physician at once. For information on treatment, within North America call (202) 625-3333 collect. Ingestion may lead to serious injury or death. Cell can explode or leak if heated, disassembled, shorted, recharged, exposed to fire or high temperature or inserted incorrectly. Keep in original package until ready to use. Do not carry batteries loose in your pocket or purse.
<b>6. Fire Hazard &amp; Firefighting</b>	
<b>Fire Hazard</b>	Batteries may rupture or leak if involved in a fire.
<b>Extinguishing Media</b>	Use any extinguishing media appropriate for the surrounding area. For incipient (beginning) fires, carbon dioxide extinguishers or copious amounts of water are effective in cooling burning lithium metal batteries. If fire progresses to where lithium metal is exposed (deep red flames), use a Class D extinguisher suitable for lithium metal.
<b>Fires Involving Large Quantities of Batteries</b>	Large quantities of batteries involved in a fire will rupture and release irritating fumes from thermal degradation
<b>7. Handling &amp; Storage</b>	
<b>Handling Precautions</b>	Avoid mechanical and electrical abuse. Do not short circuit or install incorrectly. Batteries may rupture or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions.
<b>Storage Precautions</b>	Store batteries in a dry place at normal room temperature. Refrigeration does not make them last longer.
<b>Spills of Large Quantities of Loose Batteries (unpackaged)</b>	Notify spill personnel of large spills. Irritating and flammable vapors may be released from leaking or ruptured batteries. Spread batteries apart to stop shorting. Eliminate all ignition sources. Evacuate area and allow vapors to dissipate. Clean-up personnel should wear appropriate PPE to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in appropriate container for disposal. Remove any spilled liquid with absorbent material and contain for disposal.
<b>8. Disposal Considerations (GHS Section 13)</b>	
<b>Collection &amp; Proper Disposal</b>	Dispose of used (or excess) batteries in compliance with federal, state/provincial and local regulations. Do not accumulate large quantities of used batteries for disposal as accumulations could cause batteries to short-circuit. Do not incinerate. In countries, such as Canada and the EU, where there are regulations for the collection and recycling of batteries, consumers should dispose of their used batteries into the collection network at municipal depots and retailers. They should not dispose of batteries with household trash.
<b>USA EPA RCRA (40 CFR 261)</b>	"Charged" lithium metal batteries meet the criteria (D003 - Reactivity) of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CRT 261.23. If recycled, lithium metal batteries are classified as Universal Waste.

## Article Information Sheet (AIS)

<b>USA DOT (49 CFR 173.184 (d))</b>	d) Lithium cells or batteries shipped for disposal or recycling. A lithium cell or battery, including a lithium cell or battery contained in equipment, that is transported by motor vehicle to a permitted storage facility or disposal site, or for purposes of recycling, is excepted from the testing and record keeping requirements of paragraph (a) and the specification packaging requirements of paragraph (b)(3) of this section, when packed in a strong outer packaging conforming to the requirements of §§173.24 and 173.24a. A lithium cell or battery that meets the size, packaging, and hazard communication conditions in paragraph (c)(1)-(3) of this section is excepted from subparts C through H of part 172 of this subchapter. Taping of one terminal to prevent shorting in collection bins.			
<b>US States &amp; Canada Providences</b>	California, Washington state, Washington DC prohibits disposal of batteries as trash (including household trash). Ontario, Alberta, Yukon, & British Columbia have collection bins to recycle batteries			
<b>Requirements of EU</b>	After use, the cells and/or batteries must be disposed separately from unsorted municipal waste and delivered to a commercial or authorized collection/recycling facility			
<b>Requirements of Brazil</b>	After use, the cells and/or batteries must be delivered to the commercial establishment of authorized technical assistance network.			
<b>9. Transport Information (GHS Section 14)</b>				
<b>Regulatory Status</b>	Duracell lithium metal batteries are produced and delivered in accordance with current IATA/ICAO regulations. Duracell lithium metal batteries can be shipped in accordance with ICAO/IATA. Persons who prepare or offer lithium batteries for transport are required by regulation to be trained to the extent of their responsibility. The information in this section is provided for informational purposes only. The transportation of lithium metal batteries is regulated by ICAO, IATA, IMO and US DOT. Duracell lithium metal batteries are not subject to the other provisions of the Dangerous Goods regulations as long as they are packaged and marked in accordance with the applicable regulations.			
	<b>Total Lithium Content (grams)</b>			
	<b>Catalog No.</b>	<b>Total Lithium Content (grams)</b>	<b>Type</b>	<b>Total Cell/Battery Weight (grams)</b>
	PC 123	0.55	Cell	17
	PC CR2	0.26	Cell	11
	CR17450	0.6	Cell	24
<b>UN Identification Number/ Shipping Name</b>	UN3090 Lithium metal batteries UN3091 Lithium metal batteries packed with or contained in equipment			
<b>UN 38.3 Transportation Tests</b>	UN38.3 Test Summary Documents that are required by the UN Model Regulations, can be requested by sending an email request to UN38.3_duracell@duracell.com			
<b>Special Provisions Conformance</b>	Special regulatory provisions require batteries to be packaged in a manner that prevents the generation of a dangerous quantity of heat and short circuits. Shippers can prepare batteries by taping the terminals, individually packaging batteries, or otherwise segregating the batteries to prevent risk of creating a short circuit. Batteries shipped in original unopened Duracell packaging is compliant.			
<b>Air Transport IATA 65th ed, ICAO</b>	Packaging Instructions (PI) 968-970			
<b>USA DOT SP</b>	29, A54, A100, A101			
<b>Marine/Water Transport (IMDG) SP</b>	188, 230, 310, 957			
<b>ADR/RID SP</b>	188, 230, 310, 957			
<b>ANTT (National Land Transportation Agency)</b>	Regulation 5232, 14 Dec 2016; SP 188, 230, 310, 376; Packaging Instructions P903 Complementary Instructions 5947/, 1 July 2021			

## Article Information Sheet (AIS)

Emergency Transportation Hotline	<b>CHEMTREC 24-Hour Emergency Response Hotline</b> Within the United States call +703-527-3887 Outside the United States, call +1 703-527-3887 (Collect)
<b>10. Regulatory Information (GHS Section 15)</b>	
<b>10a. Battery Requirements</b>	
USA EPA Mercury Containing & Rechargeable Battery Management Act of 1996	During the manufacturing process, no mercury is added.
EU Battery Directive 2006/66/EC & amendment 2013/56/EU	Compliant with marking and substance restrictions for mercury (<0.0005%); cadmium (<0.0020%) and lead (<0.0040%). EU retail and bulk packaging containing lithium metal batteries are marked with the special collection symbol in accordance with Article 21,
<b>10b. General Requirements</b>	
USA CPSIA 2008 (PL. 11900314)	Exempt
USA CPSC FHSA (16 CFR 1500)	Consumer batteries are not listed as a hazardous product.
USA EPA TSCA Section 13 (40 CFR 707.20)	For customs clearance purpose, batteries are defined as an "Article".
USA EPA RCRA (40 CFR 261)	"Charged" lithium metal batteries meet the criteria (D003 - Reactivity) of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.23. If recycled, lithium metal batteries are classified as Universal Waste.
USA California Prop 65	No warning required per 3rd party assessment.
CANADA Products Containing	Mercury free
EU REACH SVHC Communication	<u>SVHC Substance Name:</u> 1,2-dimethoxyethane (EGDME) <u>Use:</u> Incorporated in a lithium battery as electrolyte solvent <u>EINEC Number:</u> 203-794-9 <u>CAS Number:</u> 110-71-4 <u>Concentration:</u> The battery contains EGDME –SVHC in a concentration ranging from 1.0 to 5.0% by weight. Because the battery is sealed, 100% of the EGDME-SVHC is contained in the battery. <u>Safe Handling:</u> Do not open the battery or disassemble it. Do not expose to fire or high temperatures (>60°C). At end of life, the battery should be taken back to the nearest collection point established by a National Collection Scheme used for batteries.
EU POP regulation (Regulation (EU) 2019/1021) and their attendant amendments	Duracell cells and batteries do not contain Persistent Organic Pollutants
Japan: JIS C 8513:2020	Safety of primary lithium batteries, 2020 which specifies the necessary requirements and test methods to ensure safety during intended use and reasonably foreseeable misuse of lithium primary batteries.
<b>10c. Regulatory Definitions - Articles</b>	
USA OSHA	29 CFR 1910.1200(b)(6)(v)
USA TSCA	40 CFR 704.3; 710.2(3)(c); and [19 CFR 12.1209a]
EU & UK REACH	Title 1 - Chapter 2 - Article 3(3)
GHS	Section 1.3.2.1
<b>11. Other Information</b>	
<b>11a. Certification &amp; 3rd Party Approvals</b>	
UL Listing	Lithium Batteries - Component BBCV2.MH12538
<b>11b. AIS Hazard Communication Approaches (consulted in developing this document):</b>	

## Article Information Sheet (AIS)

<p><b>Globally Harmonized System (GHS)</b></p>	<p>GHS SDS requirements and classification criteria do not apply to articles or products (such as batteries) that have a fixed shape, which are not intended to release a chemical. The article exemption is found in Section 1.3.2.1.1 of the GHS and reads: <b><i>The GHS applies to pure substances and their dilute solutions and to mixtures. "Articles" as defined by the Hazard Communication Standard (29 CFR 1900.1200) of the OSHA of the USA, or by similar definition, are outside the scope of the system.</i></b></p>
<p><b>Joint Article Management Promotion Consortium JAMP</b></p>	<p>JAMP is a Japanese Industry Association who developed the concept of an Article Information Sheet as a supply chain tool to share and communicate chemical information in articles. The AIS authoring process is based on "declarable" substances to meet global regulatory requirements as well as substances to be reported by GADSL, JIG, etc.</p>
<p><b>IEC 62474 Ed. 1.0 B:2012 Material Declaration for Products of and for the Electro-technical Industry</b></p>	<p>An international standard that came into effect in March 2012 concerning declaration for electrical and electronic products. IEC 6274 replaces the defunct Joint Industry Guide – Material Declaration for Electro-technical Products.</p>
<p><b>IEC 62474 Database - Publically available online (<a href="http://std.iec.ch/iec62474">http://std.iec.ch/iec62474</a>). Maintained by TC11: Environmental Standardization for electrical and electronic products and systems.</b></p>	<p>The general principle for a substance to be included in the database as a declarable substance is: 1) existing national laws or regulations in an IEC member country that are relevant to Electro-technical products and that prohibit or restrict substances, or that have a labeling, communication, reporting or notification requirement, and 2) applying IEC 62474 criteria results in identification of declarable substance.</p>
<p><b>ANSI Z 400.1/Z19.1 (2010)</b></p>	<p>2.1 Scope: Applies to preparation of SDSs for hazardous chemicals used under occupational conditions. Does not address how the standard may be applied to articles. It presents basic information on how to develop and write a SDS. Additional information is provided to help comply with state and federal environmental and safety laws and regulations. Elements of the standard may be acceptable for International use.</p>
<p><b>DISCLAIMER: This AIS +C101:M106 is intended to provide a brief summary of our knowledge and guidance regarding the use of this article. The information contained here has been compiled from sources considered by Duracell to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations. This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Duracell assumes no responsibility for injury to the recipient or third persons or for any damage to any property resulting from misuse of the product.</b></p>	